



**DELTA  
FIRE**



# DF3000 TRAILER MONITOR

## KEY USERS

- Airport Fire Services
- Major Industrials
- Fuel Storage Sites
- Oil & Gas
- Petrochemicals
- Waste Recycling
- Chemical Facilities

## KEY FACTS

- Rapid Deployment
- Flows up to 3000 LPM
- Long-Reach Capabilities
- Adjustable Horizontal & Vertical Elevation
- Optional Hose racks
- Stainless Steel Chassis Versions
- UC3000 Ultra Compact Monitor Options
- 3" Waterway

Doc Ref: DDS049



**DELTA FIRE**

Wendover Road, Rackheath Industrial Estate, Norwich, Norfolk, UK NR13 6LH  
T: +44 (0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk  
[deltafire.co.uk](http://deltafire.co.uk)



## GENERAL DESCRIPTION

The Delta **DF3000 Wheeled Monitor** incorporates all the advantages of a low-friction single waterway fire monitor with the added benefit of one-man wheeled maneuverability.

The full 3" waterway provides flows of up to 3000 LPM (795 GPM) for maximised performance and incorporates the Delta DNB2600 jet/spray monitor nozzle. With full 360° rotation capabilities and adjustable elevation of 90° above and 60° below the horizontal, the DF3000 is manufactured in corrosion resistant materials and ideally suited for use on Petrochemical Refineries, Airports and any other high risk applications. Vertical and Horizontal quick-action locks allow the operator to fix the monitor swiftly to any position allowing unmanned operation.

The DF3000 is available in a number of formats including stainless steel chassis versions for extreme environment use and models fitted with Delta's new UC3000 Ultra-Compact Monitor.

Twin inlets fitted with any International adaptors allow for compatibility with existing hoselines.

## TECHNICAL DATA

Product Code	Model	Inlet	Nozzle	Maximum Flow	Rotation	Elevation	Chassis Material
MON101020	DF3000 Trailer Monitor	3" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Red Powder Coated Carbon Steel
MON101025	DF3000 Trailer Monitor	4" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Red Powder Coated Carbon Steel
MON101120	DF3000 Trailer Monitor	3" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Stainless Steel
MON101125	DF3000 Trailer Monitor	4" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Stainless Steel
MON111120	DF3000 Trailer Monitor	3" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Red Powder Coated Carbon Steel
MON111125	DF3000 Trailer Monitor	4" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Red Powder Coated Carbon Steel
MON111020	DF3000 Trailer Monitor	3" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Stainless Steel
MON111025	DF3000 Trailer Monitor	4" ANSI Flange	DNB2600 Jet/Spray Foam/Water Nozzle	3000 LPM (795 GPM)	360°	90° Above & 60° Below Horizontal	Stainless Steel

MON111120 to MON111025 use the Delta UC3000 Ultra-Compact Monitor

Length (inc Handle)	1470mm
Width	995mm
Height	610mm



### DELTA FIRE

Wendover Road, Rackheath Industrial Estate, Norwich, Norfolk, UK NR13 6LH  
 T: +44 (0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk  
[deltafire.co.uk](http://deltafire.co.uk)

