



# FIRE HOSE REELS

**BRITISH STANDARD BS EN 671-1 APPROVED**

## KEY USERS

- Major Industrials
- Marine & Off-Shore
- Petrochemicals
- Oil & Gas
- Aviation
- Nuclear
- Waste Recycling
- Civil Defence
- Construction

## KEY FACTS

- Manufactured to BS EN 671-1
- Fixed & Swinging Options
- Manual & Automatic Models
- 19mm & 25mm Tube Options
- Available as 'Drum Only' or supplied with Hose Reel Tubing
- Salt Spray Resistance Tested
- Polyester Powder Coated
- Quick, Easy Installation



**19mm & 20mm  
Hose Reel Tubing**

Doc Ref: DDS064

## GENERAL DESCRIPTION

Delta **Hose Reels** are manufactured and approved to British & European Standard BS EN 671-1 and comply fully to the stringent tests required guaranteeing excellent durability and performance.

The Hose Reel side plates are protected with a polyester powder-coating that complies with the Salt Spray Test requirements as specified in ISO 9227 requiring exposure to salt spray for 240 hours.

Delta Hose Reels have been designed to provide a flow rate of 27 LPM (7 USG) for the 19mm (3/4") and 35 LPM (9 USG) for the 25mm (1") models.

Delta provide a wide range of Hose Reels including Manual, Automatic, Swinging & Fixed options in both 19mm & 25mm models. The Automatic models have an integral valve built into the hose reel unit that opens fully after three revolutions of hose has been pulled out releasing the water stream. Once recoiled the valve shuts off automatically.


The Delta Hose Reels are supplied with a quick installation mounting bracket allowing one-man fitting.

## THE RANGE

Automatic	Swinging Product Code	Fixed Product Code	Drum Capacity	Side Plate Diameter
	FHR120030	FHR110030	30m x 3/4"	558mm (22")
	FHR140030	FHR130030	30m x 1"	558mm (22")
Manual				
	FHR115030	FHR105030	30m x 3/4"	558mm (22")
	FHR135030	FHR125030	30m x 1"	558mm (22")



Delta's **Prima Foam Units** are ideal for use with Delta Hose Reels and are easily connected to either 19mm or 25mm models. The Prima is capable of producing the equivalent fire power of 40 x standard foam extinguishers. A choice of either Low or Medium Expansion foam Prima Units are available. The Prima Combi offers both.



**DELTA FIRE**

Wendover Road, Rackheath Industrial Estate, Norwich, Norfolk, UK NR13 6LH  
T: +44 (0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk  
[deltafire.co.uk](http://deltafire.co.uk)

