



FLANGE ANSI 3" or 4" RF

18	1	GROOVED COUPLING 4" DN100	CARBON STEEL/RUBBER
17	4	PIPE FASTENING BRACKETS	CARBON STEEL
16	2	CHECK VALVE 2"1/2	BRASS
15	1	1" Gas WATER DRAIN VALVE	BRASS
14	1	WATER SUPPLY CONNECTION 2"x2,5" GAS (or BSP)	BRASS
13	1	FILLING MANHOLE COVER WITH VENT VALVE	PLASTIC MATERIAL
12	1	MOUNTING FLANGE FOR MONITOR FLANGE ANSI 4" RF	CARBON STEEL
11	1	LATERAL HOSE BOXES	CARBON STEEL
10	4	ADJUSTABLE PARKING RODS	CARBON STEEL
9	4	REFLECTORS (OPTIONAL LIGHTING SYSTEM)	PLASTIC MATERIAL
8	1	ROTATING ADJUSTABLE FRONT WHEEL	CARBON STEEL
7	1	RIGID SINGLE AXLE	CARBON STEEL
6	1	MECHANICAL STATIONARY BRAKE	CARBON STEEL
5	1	TOWING RING $\phi 45$ mm	CARBON STEEL
4	1	FOAM CONCENTRATE SUCTION 3/4" or 1/2" BSP	CARBON STEEL
3	1	FOAM TANK CAPACITY 2000Lt.	C.S. / S.S. OPTIONAL
2	1	PLATFORM CORRUGATED SHEET	ALLUMINUM
1	1	TRAILER c/w BRAKE	CARBON STEEL
POS.	Q.TY	DESCRIPTION	MATERIAL

CONSTRUCTION FEATURES	
MAXIMUM WORKING PRESSURE	7 bar
MAXIMUM ALLOWABLE FOLW	2700 Lt./min.
MAXIMUM SPEED	40 KM/h
TANK CAPACITY	2000 LITRES
PAINTED RED RAL 3000	120 micron
WEIGHT (EMPTY)	~600 Kg.

WARNING: TRAILER NOT APPROVED FOR PUBLIC ROAD USE

DELTA FIRE MONITOR TRAILER WITH TANK
2R-2000-STANDARD

Scale	1:15	12	12-40
Date	20/11/2018	Material	
Dis.	F.M.	SEE TABLE	
Contr.	A.L.	Dis. Nr.	
Toll	$\pm 2\%$ -Js13	Finish	
		PAINTED RED RAL 3000	
		12_40_000	

Index Description
Data modifica
Date mod 21/11/2018 F.M. FIRST EMISSION
Sg
MODI