

**DELTA
FIRE**



FLOOR-BELOW FIRE NOZZLE

SPECIALIST HIGH RISE NOZZLE

KEY USERS

- Municipal Fire & Rescue Services
- Industrial Fire & Rescue Services
- Defence Fire & Rescue Services

KEY FACTS

- Manufactured in the UK
- ISO9001 Quality Controlled
- Designed for use in High-Rise Buildings
- Enhanced Fire Fighter Safety
- Combats Wind-Driven Fires



Floor Below Nozzle in Action

Doc Ref: DDS036

DELTA FIRE

Wendover Road, Rackheath Industrial Estate, Norwich, Norfolk, UK NR13 6LH
T: +44 (0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk
deltafire.co.uk



GENERAL DESCRIPTION

It is widely recognised that one of the greatest dangers facing fire crews when dealing with High Rise fires is the effect of wind. Once the windows have gone, the wind will enhance the fire and rapidly increase the temperature making it virtually impossible to enter the room from an adjacent corridor or landing.

Extensive trials were carried out at West Midlands FRS training facility at Oldbury where a first floor room was taken to 600 degrees in a controlled fire situation. Using the Floor Below Nozzle, from the room below, the temperature was reduced to 90 degrees in just 20 seconds without a single fire fighter entering the test room.

The Floor Below Nozzle is specifically designed to be long enough to protrude out of a lower window where the long, angled barrel is raked upwards, firing a solid jet of water through the upper window, hitting the ceiling and rapidly gas cooling prior to fire crew entry. This is a major step forward in High Rise fire fighter safety and significantly reduces the risks associated with rising room temperatures.

Supplied a standard with 2½" Instantaneous Male or BSP threaded inlet fitting the Floor Below is fully sectional for ease of transport and independently controlled via a lever-operated ball valve.



SPECIFICATION

Manufactured in the UK

Material:	High Grade Alluminium
Length:	3.16m Overall
Weight:	9.8 KG
Inlet:	2½" Instantaneous Male or BSP Thread
Flow Rate:	470 LPM (125 GPM) @ 4 Bar
Tip Size:	22mm
Sections:	3 (Quick Release Fittings)
Bend Pitch:	60° Rake from Main Stem
Control:	Lever-Operated Ball Valve
Bend Lift:	630mm from Main Stem
Handles:	795mm from Base



DELTA FIRE

Wendover Road, Rackheath Industrial Estate, Norwich, Norfolk, UK NR13 6LH
T: +44 (0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk
deltafire.co.uk





DELTA FIRE

Wendover Road, Rackheath Industrial Estate, Norwich, Norfolk, UK NR13 6LH
T: +44 (0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk
deltafire.co.uk





DELTA FIRE

Wendover Road, Rackheath Industrial Estate, Norwich, Norfolk, UK NR13 6LH
T: +44 (0)1603 735000 | E: sales@deltafire.co.uk | E: export@deltafire.co.uk
deltafire.co.uk

