

# RAMFAN WATER DRIVEN PPV FANS

# WF20 / WF390

### **KEY USERS**

- Naval Fleets
- Defence Sectors
- Fire & Rescue Services
- Industrial & Utilities
- Marine & Off-Shore
- Mining

#### **KEY FACTS**

- Water Driven
- Unlimited Run Times
- AMCA Certified Airflows
- As Used by Global Naval Fleets (WF20) for over 20 years
- Low Maintenance
- Rugged Construction



WF390 RamFan

Doc Ref: DDS094





## **GENERAL DESCRIPTION**

Delta Fire have a long heritage of supply of the water driven RamFan's to some of the largest global Naval Fleets. No portable blower in the world compares to the smoke removal rates of the RamFan WF20 when connected to 10" or 12" Ducting.

Warships require powerful suction to remove smoke from internal spaces deep within the ship and traditionally the WF20 is fitted with multiple interconnectable lengths of ducting to access hard to reach compartments quickly and efficiently entraining smoke out of the ship into the open air.

The WF20 uses the water pressure of a fire hose and patented turbine coupled to a highly efficient fan blade to generate high-velocity, high-pressure airflow. Manufactured in corrosion resistant materials the WF20 requires infrequent and simple maintenance.

The smaller WF390 PPV fan provides lightweight wheeled portability and an impressive 17,417 cfm airflow and is ideally suited to any applications where a pressurised water supply exists.

# TECHNICAL DATA

WF390 40cm (16") Water Driven PPV			Product Code: MIS040000				
Motor	Noise Level	Airflow	Runtime	Impeller	Weight	Dims	
		(AMCA Certified)	@ max speed			(cm)	
2.1HP / 1.6kW	91 dB@ 1 m	17,417 m³/hr	Unlimited	7-Blade	27kg	58 x 43 x 41	
	86 dB @ 3 m			Turbo-Force			

WF20 20cm (8") Water Driven PP	Product Code: MIS050000A				
WF20 Ducting	Product Code: HOM000040				
Motor	Airflow	Pressure/Flow	Run Time	Weight	Dims
	(AMCA Certified)				(cm)
4.6HP@10 bar /	28,069 m³/hr @17 bar	110lpm @ 2.7 bar	Unlimited	15.9kg	40 x 31 x 31
8.0HP@17 bar		280lpm @ 17 bar			
RamFan WF20 to Royal Navy Spe					
2 ½" Instantaneous Inlet/Outlet /	NSN: 0565 /4140-99-051-5733				
Flammable Gasses (Electrical Con-					
WF20 Ducting (5m x 300mm) - 4	NSN: 0565 /4130-99-930-5937				







WF20 Ducting (5m x 300mm)



